



TLM Perforated Sheets

List of Hole Diameters & Pitches Available for Round Hole Perforation

Pattern: 60 degree staggered

Hole Diameter (mm)	Pitch (mm)	Open Area (%)	Approx Holes Per 25 mm Sq	Thickness (mm)
1.50	2.50	32.6	115.3	1.0
1.50	4.50	10.1	35.7	1.0
2.00	3.20	35.4	70.4	1.2
2.00	3.50	29.6	58.8	1.0
2.00	3.50	29.6	58.8	1.5
2.00	5.80	10.8	21.5	1.2
2.00	6.00	10.1	20.0	1.0
2.00	6.06	9.9	20.1	1.5
2.00	4.50	17.9	35.6	2.0
2.00	7.79	6.0	11.9	2.0
2.00	5.50	12.0	23.9	2.0
2.00	9.53	4.0	8.0	2.0
2.40	4.80	22.7	31.4	0.5
2.40	4.8	22.7	31.4	1.0
2.50	4.04	34.7	44.2	0.5
2.50	4.04	34.7	44.2	1.0
2.50	12.00	3.9	5.0	1.5
2.80	4.50	35.0	35.5	1.0
3.00	4.51	40.1	35.5	0.4
3.00	4.51	40.1	35.5	0.7
3.00	8.00	12.8	11.3	0.5
3.00	5.00	32.6	28.8	1.0
3.00	5.00	32.6	28.8	1.5
3.00	4.50	40.3	35.6	0.7
3.00	5.00	32.6	28.8	0.7
3.00	5.00	32.6	28.8	0.8
3.00	8.66	10.9	9.6	1.5
3.00	5.00	32.6	28.8	2.0
3.00	8.66	10.9	9.6	2.0
3.00	6.00	22.7	20.0	2.0
3.00	5.00	32.6	28.8	1.5
3.00	6.00	22.7	20.0	1.0
3.00	6.00	22.7	20.0	1.5
3.00	8.00	12.8	11.3	2.0
3.00	9.00	10.1	8.9	3.0
3.00	9.00	10.1	8.9	2.0



CERT NO. : SNG 0160395

TECK LEONG & 德隆 are registered trademarks of TECK LEONG METALS PTE LTD

Office : Blk 28 Kelantan Road #01-127 Singapore 200028
Warehouse I : 1783 Geylang Bahru #01-05 Kallang Distripark S(339708)
Warehouse II : 1783 Geylang Bahru #01-07 Kallang Distripark S(339708)
Email : sales@teckleongmetals.com

ROC : 200004371G



Hole Diameter (mm)	Pitch (mm)	Open Area (%)	Approx Holes Per 25 mm Sq	Thickness (mm)
3.00	10.00	8.2	7.3	2.0
3.00	11.00	6.7	5.9	0.9
3.00	12.50	5.2	4.6	0.7
3.20	4.50	45.9	35.7	1.0
3.20	5.00	37.1	28.8	1.0
3.30	4.90	41.1	30.0	0.4
3.30	4.90	41.1	30.0	0.7
3.30	4.90	41.1	30.0	1.0
3.30	4.90	41.1	30.0	1.2
3.45	5.18	40.2	26.9	0.5
3.50	5.00	44.4	28.8	1.0
3.50	6.00	30.9	20.1	2.0
3.60	5.00	47.0	28.9	1.2
3.60	6.00	32.6	20.1	1.0
3.60	8.66	15.7	9.6	1.5
3.60	4.35	62.0	38.1	1.5
3.70	5.49	41.2	23.9	0.4
3.70	5.49	41.2	23.9	0.7
3.95	5.89	40.8	20.8	0.4
3.95	5.89	40.8	20.8	0.7
4.00	6.50	34.3	17.1	0.6
4.00	6.00	40.3	20.0	2.0
4.00	6.00	40.3	20.0	3.0
4.00	10.39	13.4	6.7	3.0
4.00	6.20	37.7	18.7	1.5
4.00	8.00	22.7	11.3	1.5
4.00	8.00	22.7	11.3	0.8
4.00	8.00	22.7	11.3	3.0
4.00	8.50	20.1	10.0	2.0
4.00	9.00	17.9	8.9	3.0
4.00	9.00	17.9	8.9	2.5
4.00	10.39	13.4	7.0	2.0
4.00	16.4	5.4	2.7	2.0
4.00	10.39	13.4	6.7	2.0
4.00	11.00	12.0	6.0	4.0
4.00	7.00	29.6	14.7	3.0
4.00	12.00	10.1	5.0	1.5
4.00	12.00	10.1	5.0	3.0
4.00	12.18	9.8	4.9	3.0
4.00	12.23	9.7	4.9	2.0
4.00	12.18	9.8	4.9	1.5



CERT NO. : SNG 0160395

TECK LEONG & 德隆 are registered trademarks of TECK LEONG METALS PTE LTD

Office : Blk 28 Kelantan Road #01-127 Singapore 200028
 Warehouse I : 1783 Geylang Bahru #01-05 Kallang Distripark S(339708)
 Warehouse II : 1783 Geylang Bahru #01-07 Kallang Distripark S(339708)
 Email : sales@teckleongmetals.com

ROC : 200004371G



Hole Diameter (mm)	Pitch (mm)	Open Area (%)	Approx Holes Per 25 mm Sq	Thickness (mm)
4.00	12.29	9.6	4.8	3.0
4.00	14.00	7.4	3.7	4.0
4.00	20.00	3.6	1.8	1.0
4.00	17.32	4.8	2.4	1.0
4.00	30.00	1.6	0.8	1.0
4.15	6.07	42.4	19.6	0.4
4.15	6.07	42.4	19.6	0.7
4.50	6.00	51.0	20.0	1.2
4.50	6.58	42.4	16.7	0.4
4.50	6.58	42.4	16.7	0.7
4.70	6.81	43.2	15.6	0.4
4.70	6.81	43.2	15.6	0.7
4.70	7.00	29.6	10.7	3.0
4.70	7.00	29.6	10.7	1.2
4.80	6.35	51.8	17.9	0.5
4.80	6.35	51.8	17.9	1.0
5.00	7.53	40.0	13.0	1.0
5.00	7.00	46.3	14.7	1.0
5.00	6.50	53.7	17.1	1.5
5.00	6.50	53.7	17.1	1.2
5.00	7.00	46.2	14.7	1.5
5.00	8.00	35.4	11.3	1.0
5.00	8.00	35.4	11.3	4.0
5.00	13.86	11.8	3.80	4.0
5.00	8.00	35.4	11.3	3.0
5.00	13.86	11.8	3.80	3.0
5.00	10.00	22.7	7.20	1.5
5.00	10.00	22.7	7.20	2.5
5.00	12.00	15.7	5.00	3.0
5.00	12.00	15.7	5.00	2.0
5.35	7.77	43.0	12.0	0.4
5.35	7.77	43.0	12.0	0.7
6.00	7.87	52.7	11.6	0.4
6.00	7.87	52.7	11.6	0.7
6.00	7.87	52.7	11.6	1.0
6.00	12.13	22.2	4.9	1.5
6.00	24.0	5.7	1.2	3.0
6.00	26.0	4.8	1.1	3.0
6.75	9.67	44.2	7.7	0.4
6.75	9.67	44.2	7.7	0.7
7.00	9.32	51.2	8.3	0.4





Hole Diameter (mm)	Pitch (mm)	Open Area (%)	Approx Holes Per 25 mm Sq	Thickness (mm)
7.00	9.32	51.2	8.3	0.7
7.00	24.50	7.4	1.20	0.8
7.00	9.00	54.9	8.90	0.8
7.00	9.30	51.5	8.30	1.0
8.00	12.00	40.3	5.00	3.0
8.0	12.00	40.3	5.00	5.0
8.00	12.00	40.3	5.00	1.5
10.00	12.50	58.0	4.60	1.0
10.00	15.00	40.3	3.20	3.0
10.00	15.00	40.3	3.20	1.0
10.00	17.00	31.3	2.50	1.0
10.00	18.00	28.0	2.20	1.5
10.00	19.5	23.9	1.90	1.5
10.00	20.00	22.6	1.80	2.0
10.00	20.50	21.6	1.40	1.5
10.00	28.00	11.6	0.90	4.0
10.00	38.00	6.3	0.50	3.0
13.00	18.00	47.3	2.20	1.0
13.00	18.00	47.3	2.20	6.0
15.00	20.0	51.0	1.8	3.0
16.00	25.00	37.1	1.1	1.0
18.00	27.0	40.3	1.0	1.5
20.00	26.0	53.4	1.0	1.0
20.00	28.0	46.3	0.9	3.0

For more information on this product, kindly contact our sales office for assistance.

Disclaimer: All details are given in good faith and have been carefully checked. The values listed above represent reasonable approximations suitable for general engineering use. Due to commercial variations in composition and to manufacturing limitations, they should NOT be used for specification purposes. Only the full mill certificate can be accepted as accurate information regarding the properties of the metal supplied by TLM.



CERT NO. : SNG 0160395

TECK LEONG & 德隆 are registered trademarks of TECK LEONG METALS PTE LTD

Office : Blk 28 Kelantan Road #01-127 Singapore 200028
Warehouse I : 1783 Geylang Bahru #01-05 Kallang Distripark S(339708)
Warehouse II : 1783 Geylang Bahru #01-07 Kallang Distripark S(339708)
Email : sales@teckleongmetals.com

ROC : 200004371G